

FRESH AIR MAKEUP UNIT AQFAH SERIES

FEATURES

- Four models to choose from ranging in size from 200 to 900 CFM
- Units are constructed of corrosion resistant aluminum
- Hi-static fan motors for extensive fresh air ducting networks
- Removable access panels on both the top and sides are insulated internally to prevent external condensation
- Washable air inlet filter
- Internally mounted INCOLOY rod type heating elements for cold weather operation down to 23 deg Fahrenheit (-5 deg Centigrade)
- Modulating chillwater flow valve for precise air temperature control in the cooling mode
- Modulating SCR heater element control for precise air temperature control in the heating mode
- Insulated and internally coated aluminum drain pan with ant-slosh foam media inside
- Condensate outlets on both sides of the fan coil
- All unit coil assemblies are pressure tested to assure leak-proof performance
- All units are test run to assure proper operation and air flow output

AQFAH UNIT SPECIFICATIONS

SPECIFICATION		02	04	06	09
NOMINAL CAPACITY	CFM CMH	200 340	400 680	600 1020	900 1530
WEIGHT	LBS KGS	45.0 20.5	55.0 25.0	59.0 26.8	63.0 28.6
LENGTH	IN MM	34 864			
WIDTH	IN MM	23-3/4 603			
HEIGHT	IN MM	11-3/4 299	21-3/16 538		
POWER SUPPLY		208-230 / 1/ 60 200-220 / 1 / 50			
AMP DRAW @ 230-1-60		10.4	19	28	42
POWER	w	2460	4437	6644	10056
STANDARD HEATER SIZE	KW	2	4	6	9
CHILLWATER INLET / OUTLET	FPT	1/2"	3/4"	1"	1"
CHILLWATER FLOW	GPM LPM	5.3 19.9	10.5 39.8	15.8 59.8	23.7 89.7
DUCT CONNECTION	IN MM	5-7/8 x 10-1/4 149 x 260	10-7/16 x 11-15/16 265 x 303		
MINIMUM INTAKE GRILLE	IN ² CM ²	60 390	120 775	180 1160	270 1740
DRAIN FITTING	FPT	3/4" 2 / UNIT			
MAIN BREAKER SIZE		15A	25A	35A	50A

80948.WPD

AQUA-AIR MANUFACTURING, division of the James D. Nall Co., Inc. 1050 East 9th Street, Hialeah, Florida 33010 U.S.A. Ph. 305-884-8363 Fax 305-883-8549 Email sales@aquaair.com

